adjustable self-refilling microdispenser pipette

Acura® manual 865

Hand-held, self-refilling microdispenser intended for repeat distribution of microliter volumes. Carefully selected materials ensure durability and resistance to aggressive media.

Three models cover the range from 5 to 1000 µL.

Product advantages


- Excellent ergonomics, soft plunger activation
- Large volume display
- Easy in-lab calibration
- No need for consumables
- Autoclavable fully assembled at 121°C
- Versatile feeding options (Items to be ordered separately, see accessories)





100-1





Including: 90 cm silicone tubing, SS blunt end cannula, inlet valve cap, Q.C. certificate and operating instructions

Volume µL	Division µL	Inaccuracy (E%)			Imprecision (CV%)			Cat. No.
		Min. vol.	Mid. vol.	Max. vol.	Min. vol.	Mid. vol.	Max. vol.	
5 - 50	0.1	< +/- 5.0 %	< +/- 3.5 %	< +/- 1.5 %	< 2.0 %	< 1.4 %	< 0.4 %	865.0050
20 - 200	0.2	< +/- 2.5 %	< +/- 1.8 %	< +/- 1.0 %	< 1.5 %	< 1.0 %	< 0.3 %	865.0200
100 - 1000	1.0	< +/- 1.5 %	< +/- 1.1 %	< +/- 0.6 %	< 0.6 %	< 0.4 %	< 0.2 %	865.1000

Performance values obtained with bi-dest, water at constant temperature (± 0.5°C) comprised between 20 and 25°C in accordance with EN ISO 8655.

Ordering information - Accessories

Description	Pack.	Cat. No.
Reservoir with Luer connector, PP, 30 mL	1 / pk	1.861.631
• Reservoir with Luer connector, PTFE, 30 mL	1 / pk	1.861.21T
Vial holder with feed needle and lock	1 / pk	1.861.925
• Inlet valve cap, female Luer (for plastic syringe)	1 / pk	1.861.720
Stainless steel cannulas: see selection in web site		
PTFE delivery cannula	1 / pk	1.861.E32
6 Manifold, 4-channel, LL, stainl. steel, autocl.	1 / pk	1.170.054
6 Manifold, 8-channel, LL, stainl. steel, autocl.	1 / pk	1.170.058
Work station 340 for 3 microdispenser	1 / pk	320.340



For more information or for an overview of the complete Socorex product range, type www.socorex.com





865 E - B1108